ThinkPad E14 Gen 2 (Intel) Platform Specifications

	Processor		iitoi O	010 107								Smart card reade	TINONE
		# OI	# of	Bas		/lax Tur	ocessor Turbo Cache Memory			Proc	essor	Media reader	None
	Number		Threads			Freque			Types	Gra	phics	Ports	One Thunderbolt 4 / USB4 40Gbps (with the function of PD 3.0 and DP 1.4), one USB 3.2 Gen 1 (Always On), one USB 2.0, HDMI 1.4b, Ethernet (RJ-45),
	i3-1115G4	4 2	4	3.0 G	iHz	4.1 GF	łz 6ME	3			UHD phics		headphone / microphone combo jack, security keyhole
	i5-1135G7	7 4	0	2.4 G	iHz	4.2 GF	lz 8ME	DE)R4-3200		ris® Xe	Monitor cable	* Depending on many factors, actual data transfer speed may be lower than theoretical speed None
	i7-1165G7	7 4	8	2.8 G	iHz	4.7 GF	łz 12M	В			phics	Bundled Accy	None
	Integrated Graphics Discrete Graphics (Memory) Intel UHD Graphics -											Camera	One of the following, configurable by model: • HD720p camera with ThinkShutter camera privacy, fixed focus
	Intel Iris Xe Graphics NVIDIA® GeForce® MX350 (2GB GDDR5)											 IR camera and HD720p camera with ThinkShutter camera privacy, fixed focus HD Audio, Realtek ALC3287 codec, HARMAN speakers, 2W x 2, Dolby Audio™, dual array microphone, headphone / microphone combo jack 	
	Intel Iris Xe Graphics NVIDIA GeForce MX450 (2GB GDDR5)												
:	Supports up to 3 independent displays via native display and two external monitors; supports external monitors via HDMI (up to 4096x2160@30Hz) or Thunderbolt™ (up to 5120x3200@60Hz)										onitors;	Keyboard UltraNay™	6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, optional LED backlight TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad
Chipset	Intel SoC (System on Chip) platform											Security	Power-on password, hard disk password, supervisor password, security keyhole
Memory	32GB max / 3200MHz DDR4, one DDR4 SO-DIMM slot											Security chip	Discrete TPM 2.0, TCG Certified Firmware TPM 2.0 integrated in chipset
Display	Size Res	solution		Surface	Touch	Туре	Brightness	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	System Mgt	None
	14.0" FHI	D /1000v1	000) A	nti alaza		TN	220 nits			45%	90°	Fingerprint reader NFC	r Optional: Touch style fingerprint reader on power button None
	14.0 FAL	J (1920X1	080) A	nu-giare	-	IIN	220 HIIS	16:9	500:1	NTSC	90*	Battery	Integrated Li-Polymer 45Wh battery.
	14.0" FHI	D (1920x1	080) A	nti-glare	-	IPS	250 nits	16:9	800:1	45% NTSC	170°	Max battery life	supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter MobileMark® 2014: 11.9 hr
	14.0" FH	D (1920x1	080) A	nti-glare	-	IPS	300 nits	16:9	1200:1	100% sRGB	170°	Wax battery inc	MobileMark 2018: 8.7 hr * Battery life varies significantly with hardware configurations, settings, usage, & other factors
	14.0" FH	D (1920x1	080) A	nti-glare	Multi- touch	IPS	300 nits	16:9	800:1	45% NTSC	170°	AC adapter	65W USB-C AC adapter
Multi-touch(opt)	Capacitive-type on-cell multi-touch, supports 10 fingers gesture											Operating system (optional)	Windows® 10 Home 64 Windows 10 Pro 64
Storage	Up to two drives, M.2 2280 slot supports PCIe 4.0 x 4											Limited warranty • 1-year mail-in repair service	
	 M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 4 M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4 											(optional)	 1-year depot repair service 1-year depot with 2-year system board repair service
	None												1-year limited onsite service
Ethernet	Gigabit Ethernet Connection, Realtek RTL8111H											Mil-Spec test	MIL-STD-810H military testing
Bluetooth™	One of the following, configurable by model: Intel Wireless-AC 9560, Wi-Fi 2x2 802.11ac + Bluetooth 5.1, M.2 card Intel Wi-Fi 6 AX201, Wi-Fi 2x2 802.11ax + Bluetooth 5.1, M.2 card Intel WiFi 6 full features might be limited by country level restrictions											Environment	EPEAT™ Gold; ENERGY STAR® 8.0; ErP lot3; TCO Certified; RoHS-compliant; TUV Low Blue Light certified
	* BT5.1 is	supported	on Wir	idows 10	versio	n 2004	or above (li	mited to	BT5.0 on	earlier v	version)		
	None None												
Dimensions	Case Material Dimensions (WxDxH)												
	Aluminiun	n		12.76"	x 8.66"	x 0.70	"; 324	4mm x 2	20mm x 1	7.9mm			
	PC/ABS			12.76"	x 8.66"	x 0.78	"; 324	4mm x 2	20mm x 1	9.9mm			
	Aluminium (top) + PC/ABS (bottom) 12.76" x 8.66" x 0.74"; 324mm x 220mm x 18.9mm								20mm x 1	8.9mm			
Weight	Case Material Weight												
	Aluminium starting at 3.62 lb / 1.64 kg												
	PC/ABS starting at 3.73 lb / 1.69 kg												
	Aluminium (top) + starting at 3.51 lb / 1.59 kg												
Case material	Black or mineral metallic Display cover: Aluminium or PC/ABS plastic; Bottom: Aluminium or PC/ABS plastic												