

### Overview

### cHP EliteBook 645 14 inch G10 Notebook PC



#### Left

- |   |  |
|---|--|
| 1. Internal Microphones (2)                       | 7. Clickpad  |
| 2. Webcam LED (Optional)                          | 8. Smartcard Reader (Optional)                                     |
| 3. SMP IR, HD TNR and HD TNR+IR Camera (Optional) | 9. SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1) |
| 4. Camera Shutter (Only available with webcam)    | 10. Ethernet Port (RJ-45)  |
| 5. IR Camera LED (Optional)                       | 11. Nano Security Lock Slot (Lock sold separately)                 |
| 6. NFC Sensor                                     |  |

### Overview



#### Right

- |   |   |
|---|---|
| <b>1.</b> Power Button Key  | <b>6.</b> SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1) |
| <b>2.</b> Speakers  | <b>7.</b> HDMI 2.1 Port (Cable not included)                              |
| <b>3.</b> Power Connector   | <b>8.</b> Audio Combo Jack  |
| <b>4.</b> SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) | <b>9.</b> External SIM Card Slot (Optional)                               |
| <b>5.</b> SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1)                     | <b>10.</b> Touch Fingerprint Sensor (Select Models)                       |

### Overview

#### At a Glance

- Choice of AMD Barcelo™ 7000 series mobile processors, R7, R5 and R3
- Preinstalled with Windows 11 Pro, other Windows OS or FreeDOS
- Fast and upgradeable dual channel DDR4 SODIMM memory up to 64 GB
- Choice of 35.56 cm (14") diagonal HD, Ultra-Wide Viewing Angle FHD, Touch or Non-Touch screen, and Privacy Panel option
- Features quiet and responsive HP Keyboard with the HP Programmable key and backlit options
- Choice of solid state drives up to 2 TB
- Multi-layered security with HP SureStart Gen7, HP Privacy Camera, HP Sure View, HP Sure Sense, HP Sure Click, HP Secure Erase, Sure Run Gen5, Sure Recover Gen5, Touch Fingerprint reader, and Tamper Lock
- Supports wireless options for connectivity on the go including gigabit-speed Wi-Fi 6E and CAT16 4G/LTE WWAN
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles
- Designed to support HP docking options
- Passed MIL-STD 810H tests <sup>1</sup>
- Battery life up to 16 hours 30 minutes with the optional 51.3Whr battery
- Optimize your video calls with a 5MP+IR camera, HD+IR/HD camera and temporal noise reduction that adjusts to the lighting in your environment.
- 180° synchronized hinge allows the EliteBook to lay completely flat, without lifting the keyboard, and includes everyone with visibility from multiple angles.
- Can be wiped up to 1000 times with common household cleaning wipes<sup>2</sup>
- Synchronized hinge allows the EliteBook to ProBook to open to 177° +/- 3° without lifting the keyboard and offers visibility from multiple angles.

1. MIL-STD 810H is not intended to demonstrate fitness of U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

2. See wipe manufacturer's instructions for disinfecting and the HP cleaning guide for HP tested wipe solutions at <http://h20195.www.2.hp.com/v2/GetDocument.aspx?docname=4AA7-7610ENW>

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

## Technical Specifications

### PRODUCT NAME

HP EliteBook 645 14 inch G10 Notebook PC

### OPERATING SYSTEMS

#### Preinstalled

Windows 11 Pro <sup>1</sup>  
 Windows 11 Pro Education <sup>1</sup>  
 Windows 11 Home - HP recommends Windows 11 Pro for business <sup>1</sup>  
 Windows 11 Home Single Language - HP recommends Windows 11 Pro for business <sup>1</sup>  
 Windows 11 Pro (Windows 11 Enterprise or Windows 10 Enterprise available with a Volume Licensing Agreement) <sup>1</sup>  
 Windows 11 Pro (preinstalled with Windows 10 Pro Downgrade) <sup>1,2</sup>  
 FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

### PROCESSORS

Processor <sup>3,4</sup>	Cores	Threads	L3 Cache	Max Boost Frequency <sup>5</sup>	Base Frequency	Pro
AMD Ryzen™ 7 PRO-7730U	8	16	16MB	4.50GHz	2.00GHz	X
AMD Ryzen™ 7-7730U	8	16	16MB	4.50GHz	2.00GHz	
AMD Ryzen™ 5 PRO-7530U	6	12	16MB	4.50GHz	2.00GHz	X
AMD Ryzen™ 5-7530U	6	12	16MB	4.50GHz	2.00GHz	
AMD Ryzen™ 3-7330U	4	8	8MB	4.30GHz	2.30GHz	

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. AMD Max Boost frequency performance varies depending on hardware, software and overall system configuration.

## Technical Specifications

### CHIPSET

Chipset is integrated with processor

---

### GRAPHICS

#### Integrated

AMD Radeon™ Graphics

---

### DISPLAY

#### Non-Touch

35.6 cm (14") diagonal FHD UWVA eDP anti-glare, IPS, micro-edge, Narrow Bezel Bent, 250 nits, 45% NTSC for HD + IR camera and WWAN (1920 x 1080) <sup>6,7,8</sup>

35.6 cm (14") diagonal FHD UWVA eDP anti-glare, IPS, Low Blue Light, 400 nits, 100% sRGB for 5MP + IR camera (1920x1080) with HP Eye Ease <sup>6,7,8</sup>

35.6 cm (14") diagonal, FHD UWVA eDP1.4 w/o PSR, anti-glare, Narrow Bezel Bent, 250 nits, 45%, no mic and WWAN (1920 x 1080) <sup>6,7,8</sup>

35.6 cm (14") diagonal, FHD UWVA eDP1.4 w/o PSR, anti-glare, Narrow Bezel Bent, 250 nits, 45%, no mic (1920 x 1080) <sup>6,7,8</sup>

35.6 cm (14") diagonal FHD UWVA eDP anti-glare, Low Power, Low Blue Light, 400 nits, 100% sRGB for HD + IR camera and WWAN (1920x1080) with HP Eye Ease <sup>6,7,8</sup>

35.6 cm (14") diagonal FHD UWVA anti-glare, IPS, Low Blue Light, 1000 nits, 100% sRGB for 5MP + IR camera, HP Sure View Gen4 integrated privacy screen with HP Eye Ease (1920x1080) <sup>6,7,8,9,10</sup>

35.6 cm (14") diagonal, FHD UWVA, IPS, micro edge, eDP1.2 w/o PSR, Anti-Glare, 250 nits, 45% NTSC Narrow Bezel bent (1920x1080) <sup>6,7,8</sup>

35.6 cm (14") diagonal, FHD UWVA, eDP, IPS, micro edge, Anti-Glare, 250 nits, 45% NTSC Narrow Bezel bent for HD camera (1920x1080) <sup>6,7,8</sup>

35.6 cm (14") diagonal, FHD UWVA, eDP, IPS, micro edge, Anti-Glare, Narrow Bezel bent, 250 nits, 45% NTSC for HD camera and WWAN (1920x1080) <sup>6,7,8</sup>

35.6 cm (14") diagonal, HD SVA eDP 1.2 w/o PSR, Anti-Glare, 250 nits, 45% NTSC Narrow Bezel bent (1366x768) <sup>6,7,8</sup>

35.6 cm (14") diagonal HD SVA eDP anti-glare narrow bezel bent, 250 nits, 45% NTSC for HD Camera (1366x768) <sup>6,7,8,9</sup>

#### Touch

35.6 cm (14") diagonal, FHD UWVA, eDP, IPS, micro edge, Anti-Glare, Narrow Bezel bent touch-on-panel screen 250 nits, 45% NTSC for HD camera (1920x1080) <sup>6,7,8,10</sup>

#### Display Size (Diagonal)

14" diagonal

35.6 cm (14") diagonal

6. HD content required to view HD images.

7. Sold separately or as an optional feature.

8. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

9. HP Sure View Reflect integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

10. Actual brightness will be lower with touchscreen or Sure View.

---

## Technical Specifications

### DOCKING (Sold Separately)

<b>Docking station model #1</b>	HP Thunderbolt 120W G4 Dock
<b>Docking station model #2</b>	HP Thunderbolt 280W G4 Dock
<b>Docking station model #3</b>	HP USB-C Dock G5
<b>Docking station model #4</b>	HP USB-C/A Universal Dock G2
<b>Docking station model #5</b>	HP USB-C G5 Essential Dock

[For additional aftermarket options and docking specs please see page 42.](#)

## STORAGE AND DRIVES

### Primary Storage

- 2 TB PCIe® Gen 4x4 NVMe™ TLC 2280 Solid State Drive <sup>11,12</sup>
- 1 TB PCIe® Gen 4x4 NVMe™ TLC 2280 Self Encrypted OPAL2 Solid State Drive <sup>11,12</sup>
- 1 TB PCIe® Gen 4x4 NVMe™ TLC 2280 Solid State Drive <sup>11,12</sup>
- 512 GB PCIe® NVMe™ M.2 SSD <sup>11</sup>
- 512 GB PCIe® Gen 4x4 NVMe™ TLC 2280 Self Encrypted OPAL2 Solid State Drive <sup>11,12</sup>
- 512 GB PCIe® Gen 4x4 NVMe™ TLC Solid State Drive <sup>11,12</sup>
- 256 GB PCIe® NVMe™ M.2 SSD <sup>11,12</sup>
- 256 GB PCIe® NVMe™ Value 2280 Self Encrypted OPAL2 Solid State Drive <sup>11</sup>

### Primary M.2 Storage

- 256 GB PCIe® NVMe™ Value 2230 2nd Solid State Drive <sup>11,13</sup>

11. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

12. Only functions at the Gen3x4 capacity with AMD Ryzen Barcelo processor

13. Secondary SSD slot (M.2 2230 form factor; Optional) is used for data storage only, not used for OS deployment, and is only available with non-WWAN base Unit AND Primary M.2 storage.

## MEMORY

### Maximum Memory

- 64 GB DDR4-3200 SDRAM <sup>14</sup>

### Memory

- 64 GB DDR4-3200 SDRAM (2x32GB) <sup>14</sup>
- 32 GB DDR4-3200 SDRAM (1 x 32 GB) <sup>14</sup>
- 32 GB DDR4-3200 SDRAM (2 x 16 GB) <sup>14</sup>
- 16 GB DDR4-3200 SDRAM (1 x 16 GB) <sup>14</sup>
- 16 GB DDR4-3200 SDRAM (2 x 8 GB) <sup>14</sup>
- 8 GB DDR4-3200 SDRAM (1 x 8 GB) <sup>14</sup>
- 8 GB DDR4-3200 SDRAM (2 x 4 GB) <sup>14</sup>

### Memory Slots

- 2 SODIMM

Both slots are customer accessible / upgradeable

DDR4 PC4 SODIMMS (Barcelo runs at 3200)

### Technical Specifications

Supports Dual Channel Memory

14. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

### NETWORKING/COMMUNICATIONS

#### WLAN

Realtek RTL8852CE 802.11ax 2x2 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card <sup>15</sup>  
Mediatek RZ616 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card <sup>15</sup>

#### WWAN

Intel® XMM 7560 R+ LTE-Advanced Pro WWAN (Cat 16) <sup>16</sup>

#### NFC

NXP NPC300 Near Field Communication Module (NFC Mirage WNC XRAV-1)

#### MIRACAST

Native Miracast Support <sup>17</sup>

#### Ethernet

Realtek RTL8111FPH 10/100/1000 Integrated NIC <sup>18</sup>  
Realtek RTL8111HSH 10/100/1000 Integrated NIC (Non-DASH) <sup>18</sup>

15. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

16. Gigabit-class 4G LTE module is optional and must be configured at the factory. Module designed for up to 1 Gbps download speeds as carriers deploy 5 carrier aggregation and 100Mhz channel bandwidth, requires activation and separately purchased service contract. Backwards compatible to HSPA 3G technologies. Check with service provider for coverage and availability in your area. Connection, upload, and download speeds will vary due to network, location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

17. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

18. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

### Technical Specifications

#### AUDIO/MULTIMEDIA

**Audio**

2 Integrated stereo speakers  
Integrated microphone (Dual Array)

**Speaker Power**

2W/4ohm Per speaker

**Webcam**

720p HD camera with Temporal Noise Reduction <sup>6,7</sup>  
720p HD camera+IR Camera with Temporal Noise Reduction <sup>6,7,8</sup>  
5MP camera+IR with Temporal Noise Reduction <sup>6,7</sup>  
5 MP + IR camera for face authentication with Windows Hello

6. HD content required to view HD images.  
7. Sold separately or as an optional feature.

---

#### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

**Keyboard**

HP Premium Keyboard, spill resistant with optional backlit function <sup>19</sup>

**Pointing Device**

Clickpad with multi-touch gesture support

**Function Keys**

F1 - Display Switching  
F2 - Blank or SureView On/Off  
F3 - Brightness Down  
F4 - Brightness Up  
F5 - Audio Mute  
F6 - Volume Down  
F7 - Volume Up  
F8 - Mic Mute  
F9 - Blank or Backlit Toggle  
F10 - Insert  
F11 - Wireless  
F12 - Programmable key

**Hidden Function Keys**

Fn+R - Break  
Fn+S - Sys Rq  
Fn+C - Scroll Lock

19. Backlit keyboard is an optional feature.

---



### Technical Specifications

#### SOFTWARE AND SECURITY

##### Preinstalled Software

###### Software

HP Quick Drop <sup>20</sup>  
HP PC Hardware Diagnostics Windows  
myHP  
HP Smart Support <sup>21</sup>  
HP Services Scan <sup>22</sup>  
HP Connection Optimizer  
HP Hotkey Support  
HP Support Assistant <sup>23</sup>  
HP Notifications  
HP Privacy Settings  
HP Power Manager  
Buy Microsoft Office (Sold separately)

##### Manageability Features

HP Connect <sup>24</sup>  
HP Image Assistant Gen5 (download)  
HP Manageability Integration Kit (download) <sup>25</sup>  
HP Client Management Script Library (download)  
HP Patch Assistant (download) <sup>26</sup>  
HP Driver Packs (download)  
HP Client Catalog (download)  
HP Cloud Recovery

##### Security Management

HP Wolf Security for Business <sup>27</sup> includes:  
HP Sure Click <sup>28</sup>  
HP Sure Sense <sup>29</sup>  
HP Sure Run <sup>30</sup>  
HP Sure Recover <sup>31</sup>  
HP Sure Start <sup>32</sup>  
HP Tamper Lock  
HP Sure Admin <sup>33</sup>

##### BIOS

HP BIOSphere Gen6 <sup>34</sup>  
HP Secure Erase <sup>35</sup>  
Absolute Persistence Module <sup>36</sup>  
BIOS Update via Network  
HP Wake on WLAN  
Secured-Core PC Enable <sup>37</sup>  
TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)  
HP Fingerprint Sensor <sup>38</sup>

##### Security

###### TPM

Model: Nuvoton NPCT760HABYX  
Version: 7.2.3.1

## Technical Specifications

Revision: TPM 2.0  
FIPS 140-2 Compliant: Yes

### Smartcard Reader

Model number: Alcor AU9560  
FIPS 201 Compliant: Yes

### IPv6 Support

Yes

### FirstNet Certified

Yes

### The BIOS on this notebook implements ISO/IEC 19678:2015 guidelines (formerly NIST 800-147).

UEFI version: 2.7

Class: 3

20. HP Quick Drop requires Internet access and Windows 10 or higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.

21. HP Smart Support requires HP TechPulse to be installed. For more information about how to enable or to download HP Smart Support, please visit <http://www.hp.com/smart-support>. HP Services Scan is provided thru Windows Update and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. HP TechPulse is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements or to disable this feature, please visit <http://www.hpdaas.com/requirements>.

22. HP Services Scan is provided with Windows Update on select products and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. HP TechPulse is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements or to disable this feature, please visit <http://www.hpdaas.com/requirements>. Not applicable in China.

23. HP Support Assistance requires Windows and Internet Access

24. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.

25. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

26. HP Patch Assistant available on select HP PCs with the HP Manageability Kit that are managed through Microsoft System Center Configuration Manager. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

27. HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features and OS requirement

28. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.

29. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS25. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.

30. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.

31. HP Sure Recover is available on select HP PCs and requires an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data.

### Technical Specifications

- 32. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher
  - 33. HP Sure Admin requires Windows 10 or higher, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store
  - 34. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
  - 35. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
  - 36. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>
  - 37. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.
  - 38. HP Fingerprint sensor is an optional feature that must be configured at purchase.
-

## Technical Specifications

### POWER

#### Power Supply

AC Adapter 45 Watt nPFC Standard USB Type C® Straight 1.8m <sup>39</sup>

AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m <sup>39</sup>

AC Adapter 45 Watt Smart nPFC Standard C8 for 2 prong Barrel 4.5mm Right Angle <sup>39</sup>

AC Adapter 65 Watt nPFC Standard USB Type C® Straight 1.8m<sup>39</sup>

AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm <sup>39</sup>

AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m <sup>39</sup>

#### Battery

HP Long Life 3-cell, 42.75 Wh Polymer<sup>40,41</sup>

HP Long Life 3-cell, 51.3 Wh Polymer <sup>40,41</sup>

Compliant with UL 1642 Standard

#### Power Cord

3-wire plug - 1m <sup>39</sup>

2-wire plug - 1m <sup>39</sup>

#### Battery Life

Up to 13 hours 30 minutes with 42.75Whr battery [HP Long Life 3-Cell, 42.75Whr Polymer, UMA graphics, AMD R7 PRO, display set to 200 nits (on a 400-nit display), 2\*4G memory, 256G SSD] <sup>42</sup>

Up to 16 hours 30 minutes with 51.3Whr battery [HP Long Life 3-Cell, 51.3Whr Polymer, UMA graphics, AMD R7 PRO, display set to 200 nits (on a 400-nit display) (, 2\*4G memory, 256G SSD)]<sup>42</sup>

#### Battery Weight

HP Long Life 3-cell - 42.75 Wh Polymer - .40 lb

HP Long Life 3-cell - 51.3 Wh Polymer - .45 lb

HP Long Life 3-cell - 42.75 Wh Polymer - 181.83 g

HP Long Life 3-cell - 51.3 Wh Polymer - 203.56 g

39. Availability may vary by country.

40. Battery is internal and not replaceable by customer. Serviceable by warranty.

41. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

42. MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See [www.bapco.com](http://www.bapco.com) for additional details.

## Technical Specifications

### WEIGHTS & DIMENSIONS

**Product Weight**

Starting at 3.1 lb <sup>43</sup>

Starting at 1.4 kg <sup>43</sup>

**Product Dimensions (W x D x H)**

12.67 x 8.42 x 0.78 in

32.19 x 21.39 x 1.99 cm

**Packaging Dimensions (W x D x H) <sup>44</sup>**

12"-15" boxes (305mm height): 1200mm x 1000mm x 1080mm

43. Weight will vary by configuration. Does not include power adapter.

44. Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details.

### PORTS/SLOTS

1 SuperSpeed USB Type-C<sup>®</sup> 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)

3 SuperSpeed USB Type-A 5Gbps signaling rate Port (1 Powered port) (USB 3.2 Gen 1)

1 AC power

1 HDMI 2.1 <sup>45</sup>

1 Headphone/microphone combo jack

1 Nano SIM slot for WWAN (optional)

1 RJ-45

1 Smart Card Reader (optional)

45. HDMI cable sold separately

### SERVICE AND SUPPORT

1-year and 3-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.<sup>46</sup>

46. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit [www.hp.com/go/cpc](http://www.hp.com/go/cpc). HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

## Technical Specifications

**SYSTEM UNIT****Stand-Alone Power Requirements  
(AC Power)**

Nominal Operating Voltage	19V
Average Operating Power	7.52W (Idle)
Integrated graphics	Yes (AMD Radeon™ Graphics)
Discrete Graphics	N/A
Max Operating Power	Discrete < 65W UMA < 45W"

**Temperature**

Operating	32° to 95° F (0° to 35° C)
Non-operating	-4° to 140° F (-20° to 60° C)

**Relative Humidity**

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

**Shock**

Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine

**Random Vibration**

Operating	1.043 grams
Non-operating	3.5 grams

**Altitude (unpressurized)**

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)

**Planned Industry Standard  
Certifications**

Regulatory Model Number	HSN-Q35C-4
CSA/UL 62368-1	Yes
ENERGY STAR®	Yes <sup>47</sup>
EPEAT®	EPEAT® Gold in the United States <sup>48</sup>
FCC/ICES/CISPR/VCCI	Yes
CE MARKING	Yes
GS Mark	Yes
	Related commodity should comply with ISO 9241 Standards.
China CCC/SRRC	Yes
Taiwan BSMI/NCC	Yes
Korea KCC/KC/KES	Yes
Ukraine NSoC/TEC	Yes
EAEU Compliance	Yes
Saudi Arabian Compliance	Yes
TCO	Yes
WW RoHS	Yes
Low Blue Light	Yes

47. Configurations of the HP EliteBook 645 14 inch G10 Notebook PC that are ENERGY STAR® qualified are identified as HP EliteBook 645 14 inch G10 Notebook PC ENERGY STAR on HP websites and on <http://www.energystar.gov>.

## Technical Specifications

48. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

### DISPLAYS

1. Actual brightness will be lower with touchscreen or HP Sure View.

**NOTE:** All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

<b>Panel LCD 14 inch FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR bent Touch on Panel NWBZ</b>	<b>Outline Dimensions (W x H x D)</b>	316.170 x 186.400 (max)
	<b>Active Area</b>	309.370 x 174.020 mm (typ)
	<b>Weight</b>	305 g (max)
	<b>Diagonal Size</b>	14.0
	<b>Surface Treatment</b>	Anti-Glare On-cell
	<b>Touch Enabled</b>	Yes <sup>1</sup>
	<b>Contrast Ratio</b>	600:1 (typ)
	<b>Refresh Rate</b>	60 Hz
	<b>Brightness</b>	250 nits <sup>1</sup>
	<b>Pixel Resolution - Format</b>	1920 x 1080 (FHD)
	<b>Backlight</b>	LED
	<b>Pixel Resolution</b>	RGB
	<b>Color Gamut Coverage</b>	NTSC 45%
	<b>Color Depth</b>	6 (Hi FRC w/ condition to enable)
	<b>Viewing Angle</b>	UWVA 85/85/85/85
	<b>Low Blue Light</b>	No
	<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	2.30 (max)/ 2.80 (max)

<b>14.0 in FHD (1920 x 1080) Anti-Glare UWVA Low Blue Light sRGB NB2X 400 eDP 1.4+PSR2 Low-Power 100 bent LCD Panel</b>	<b>Outline Dimensions (W x H x D)</b>	315.100 x 184.900 (max)
	<b>Active Area</b>	309.370 x 174.020 mm (typ)
	<b>Weight</b>	230g (max)
	<b>Diagonal Size</b>	14.0
	<b>Surface Treatment</b>	Anti-Glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	1200:1 (typ)
	<b>Refresh Rate</b>	60Hz
	<b>Brightness</b>	400 nits <sup>1</sup>
	<b>Pixel Resolution - Format</b>	1920 x 1080 (FHD)
	<b>Backlight</b>	WLED
	<b>Pixel Resolution</b>	RGB
	<b>Color Gamut Coverage</b>	sRGB 100%
	<b>Color Depth</b>	8
	<b>Viewing Angle</b>	UWVA 89/89/89/89

### Technical Specifications

<b>Low Blue Light</b>	Yes
<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	1.23 (max)/1.5 (max)

<b>Panel LCD 14-in FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ bent</b>	<b>Outline Dimensions (W x H x D)</b>	316.170 x 186.400 (max)
	<b>Active Area</b>	309.370 x 174.020 mm (typ)
	<b>Weight</b>	300 g (max)
	<b>Diagonal Size</b>	14.0
	<b>Surface Treatment</b>	Anti-Glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	600:1 (typ)
	<b>Refresh Rate</b>	60Hz
	<b>Brightness</b>	250 nits <sup>1</sup>
	<b>Pixel Resolution - Format</b>	1920 x 1080 (FHD)
	<b>Backlight</b>	LED
	<b>Pixel Resolution</b>	RGB
	<b>Color Gamut Coverage</b>	NTSC 45%
	<b>Color Depth</b>	6 (Hi FRC w/ condition to enable)
	<b>Viewing Angle</b>	UWVA 85/85/85/85
	<b>Low Blue Light</b>	No
<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	2.205 (max)/ 2.716 (max)	

<b>Panel LCD 14-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ bent</b>	<b>Outline Dimensions (W x H x D)</b>	316.110 x 186.370 (max)
	<b>Active Area</b>	309.400 x 173.950 mm (typ)
	<b>Weight</b>	300 g (max)
	<b>Diagonal Size</b>	14.0
	<b>Surface Treatment</b>	Anti-Glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	300:1 (typ)
	<b>Refresh Rate</b>	60 Hz
	<b>Brightness</b>	250 nits <sup>1</sup>
	<b>Pixel Resolution - Format</b>	1366 x 768 (HD)
	<b>Backlight</b>	LED
	<b>Pixel Resolution</b>	RGB
	<b>Color Gamut Coverage</b>	NTSC 45%
	<b>Color Depth</b>	6
	<b>Viewing Angle</b>	SVA 45/45/15/35
	<b>Low Blue Light</b>	No



### Technical Specifications

<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	2.52 (max) / 2.86 (max)
---	-------------------------

<b>14.0 in FHD (1920 x 1080) Anti-Glare UWVA Low Blue Light sRGB NB2Y 1000 eDP 1.3+PSR 100 PrivacyG4 Plus bent LCD Panel</b>	<b>Outline Dimensions (W x H x D)</b>	314.612 x 185.330 (max)
	<b>Active Area</b>	309.312 x 173.990 (typ)
	<b>Weight</b>	230 g (max)
	<b>Diagonal Size</b>	14.0
	<b>Surface Treatment</b>	Anti-Glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	1500:1 (typ)
	<b>Refresh Rate</b>	60 Hz
	<b>Brightness</b>	1000 nits <sup>1</sup>
	<b>Pixel Resolution - Format</b>	1920 x1080 (FHD)
	<b>Backlight</b>	WLED
	<b>Pixel Resolution</b>	RGB
	<b>Color Gamut Coverage</b>	sRGB 100%
	<b>Color Depth</b>	8
	<b>Viewing Angle</b>	UWVA 85/85/85/85
	<b>Low Blue Light</b>	Yes
	<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	NA

### Technical Specifications

#### STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

<b>SSD 256GB 2230 PCIe NVMe Value</b>	<b>Form Factor</b>	M.2 2230
	<b>Capacity</b>	256 GB
	<b>NAND Type</b>	Value
	<b>Interface</b>	PCIe NVMe
	<b>Minimum Sequential Read</b>	2000 MB/s ± 10%
	<b>Minimum Sequential Write</b>	900 MB/s ± 10%
	<b>Logical Blocks</b>	500118192
	<b>Features</b>	Pyrite; TRIM; L1.2

<b>SSD 256GB 2280 PCIe NVMe Value</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	256GB
	<b>NAND Type</b>	Value
	<b>Interface</b>	PCIe NVMe
	<b>Minimum Sequential Read</b>	2000 MB/s ± 10%
	<b>Minimum Sequential Write</b>	900 MB/s ± 10%
	<b>Logical Blocks</b>	500118192
	<b>Features</b>	ATA Security; TRIM; L1.2

<b>256GB PCIe 2280 NVMe Self Encrypted OPAL2 Value Solid State Drive</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	256 GB
	<b>NAND Type</b>	Opal2 Value
	<b>Interface</b>	PCIe NVMe Gen4X4
	<b>Minimum Sequential Read</b>	2000 MB/s ± 10%
	<b>Minimum Sequential Write</b>	900 MB/s ± 10%
	<b>Logical Blocks</b>	500,118,192
	<b>Features</b>	Pyrite 2.0; TRIM; L1.2

<b>SSD 512GB 2280 PCIe NVMe Value</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	512GB
	<b>NAND Type</b>	Value
	<b>Interface</b>	PCIe NVMe
	<b>Minimum Sequential Read</b>	2200 MB/s ± 10%
	<b>Minimum Sequential Write</b>	1000 MB/s ± 10%
	<b>Logical Blocks</b>	1000215216
	<b>Features</b>	Pyrite 2.0, TRIM; L1.2

### Technical Specifications

<b>512GB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	512 GB
	<b>NAND Type</b>	Opal2 TLC
	<b>Interface</b>	PCIe NVMe Gen4X4
	<b>Minimum Sequential Read</b>	6400 MB/s ± 10%
	<b>Minimum Sequential Write</b>	3500 MB/s ± 10%
	<b>Logical Blocks</b>	1,000,215,216
	<b>Features</b>	Pyrite 2.0, TRIM; L1.2

<b>SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	512 GB
	<b>NAND Type</b>	TLC
	<b>Interface</b>	PCIe NVMe Gen4X4
	<b>Minimum Sequential Read</b>	6400 MB/s ± 10%
	<b>Minimum Sequential Write</b>	3500 MB/s ± 10%
	<b>Logical Blocks</b>	1,000,215,216
	<b>Features</b>	Pyrite 2.0, TRIM; L1.2

<b>1TB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	1 TB
	<b>NAND Type</b>	Opal2 TLC
	<b>Interface</b>	PCIe NVMe Gen4X4
	<b>Minimum Sequential Read</b>	6400 MB/s ± 10%
	<b>Minimum Sequential Write</b>	5000 MB/s ± 10%
	<b>Logical Blocks</b>	2,000,409,264
	<b>Features</b>	Pyrite 2.0, TRIM; L1.2

<b>SSD 1TB 2280 PCIe-4x4 NVMe Three Layer Cell</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	1 TB
	<b>NAND Type</b>	TLC
	<b>Interface</b>	PCIe NVMe Gen4X4
	<b>Minimum Sequential Read</b>	6400 MB/s ± 10%
	<b>Minimum Sequential Write</b>	5000 MB/s ± 10%
	<b>Logical Blocks</b>	2,000,409,264
	<b>Features</b>	Pyrite 2.0, TRIM; L1.2

<b>SSD 2TB 2280 PCIe-4x4 NVMe Three Layer Cell</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	2 TB
	<b>NAND Type</b>	TLC
	<b>Interface</b>	PCIe NVMe Gen4X4
	<b>Minimum Sequential Read</b>	6400 MB/s ± 10%

### Technical Specifications

<b>Minimum Sequential Write</b>	5000 MB/s $\pm$ 10%
<b>Logical Blocks</b>	4,000,797,360
<b>Features</b>	Pyrite 2.0, TRIM; L1.2

---

### Technical Specifications

#### NETWORKING/COMMUNICATIONS

<b>Realtek RTL8852CE 802.11ax 2x2 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card (802.11ax 2x2, supporting gigabit data rate)<sup>1</sup></b>	<b>Wireless LAN Standards</b>	<ul style="list-style-type: none"> <li>IEEE 802.11a</li> <li>IEEE 802.11b</li> <li>IEEE 802.11g</li> <li>IEEE 802.11n</li> <li>IEEE 802.11ac</li> <li>IEEE 802.11ax</li> <li>IEEE 802.11d</li> <li>IEEE 802.11e</li> <li>IEEE 802.11h</li> <li>IEEE 802.11i</li> <li>IEEE 802.11k</li> </ul>
	<b>Interoperability</b>	Wi-Fi certified
	<b>Frequency Band</b>	<ul style="list-style-type: none"> <li>•802.11b/g/n/ax 2.402 – 2.482 GHz</li> <li>•802.11a/n/ac/ax 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz 5.955 – 6.415 GHz 6.435 – 6.515 GHz 6.535 – 6.875 GHz 6.895 – 7.115 GHz</li> </ul>
	<b>Data Rates</b>	<ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>• 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz &amp; 160MHz)</li> <li>• 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz &amp; 160MHz)</li> </ul>
	<b>Modulation</b>	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	<b>Security <sup>2</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 (personal) certification</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> <li>• EAP</li> </ul>
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power <sup>3</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b : +17dBm minimum</li> <li>• 802.11g : +16dBm minimum</li> <li>• 802.11a : +17dBm minimum</li> </ul>

### Technical Specifications

	<ul style="list-style-type: none"> <li>• 802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +13dBm minimum</li> <li>• 802.11n HT20(5GHz) : +14dBm minimum</li> <li>• 802.11n HT40(5GHz) : +13dBm minimum</li> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT160(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE40(2.4GHz) : +12dBm minimum</li> <li>• 802.11ax HE80(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE160(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE80(6GHz) : +10dBm minimum</li> <li>• 802.11ax HE160(6GHz) : +10dBm minimum</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode :2.5 W</li> <li>• Receive mode :2 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode :50 mW (WLAN unassociated)</li> <li>• Connected Standby/Modern Standby: 10mW</li> <li>• Radio disabled: 8 mW</li> </ul>
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity</b> <sup>4</sup>	<ul style="list-style-type: none"> <li>• 802.11b, 1Mbps : -93.5dBm maximum</li> <li>• 802.11b, 11Mbps : -84dBm maximum</li> <li>• 802.11a/g, 6Mbps : -86dBm maximum</li> <li>• 802.11a/g, 54Mbps : -72dBm maximum</li> <li>• 802.11n, MCS07 : -67dBm maximum</li> <li>• 802.11n, MCS15 : -64dBm maximum</li> <li>• 802.11ac, MCS0(VHT80) : -84dBm maximum</li> <li>• 802.11ac, MCS9(VHT80) : -59dBm maximum</li> <li>• 802.11ac, MCS9(VHT160) : -58.5dBm maximum</li> <li>• 802.11ax, MCS11(HE40): -57dBm maximum</li> <li>• 802.11ax, MCS11(HE80): -54dBm maximum</li> <li>• 802.11ax, MCS11(HE160): -53.5dBm maximum</li> </ul>
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	1. Type 2230 : 2.8g 2. Type 126: 1.3g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	<b>Operating</b> 14° to 158° F (-10° to 70° C) <b>Non-operating</b> -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating</b> 10% to 60% (non-condensing) <b>Non-operating</b> 5% to 95% (non-condensing)
<b>Altitude</b>	<b>Operating</b> 0 to 10,000 ft (3,048 m) <b>Non-operating</b> 0 to 50,000 ft (15,240 m)

## Technical Specifications

**LED Activity** N/A

**HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card**

<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps BLE: 1 Mbps data rate; throughput up to 0.2 Mbps Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
<b>Power Consumption</b>	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
<b>Bluetooth Software Supported</b>	Microsoft Windows Bluetooth Software
<b>Link Topology</b>	
<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support
<b>Certifications</b>	FCC (47 CFR) Part 15C, Section 15.247 & 15.407
<b>Power Management Certifications</b>	ETS 300 328 Low Voltage Directive CE Mark
<b>Bluetooth Profiles Supported</b>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising

### Technical Specifications

- 2Mbps LE
- LE Long Range
- Windows BT profiles support
- BT5.3
- Periodic Advertisement interval
- Encryption key size control enhancements

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

**Mediatek RZ616 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card(802.11ax 2x2, supporting gigabit data rate) <sup>1</sup>**

- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.11g
- IEEE 802.11n
- IEEE 802.11ac
- IEEE 802.11ax
- IEEE 802.11d
- IEEE 802.11e
- IEEE 802.11h
- IEEE 802.11i
- IEEE 802.11j
- IEEE 802.11k
- IEEE 802.11mc
- IEEE 802.11r
- IEEE 802.11v
- IEEE 802.11w

**Interoperability  
Frequency Band**

- Wi-Fi certified
- 802.11b/g/n/ax  
2.402 – 2.482 GHz
- 802.11a/n/ac/ax  
5.15 – 5.25 GHz  
5.25 – 5.35 GHz  
5.47 – 5.725 GHz  
5.825 – 5.850 GHz  
5.925 – 7.125 GHz

**Data Rates**

- 802.11b: 1, 2, 5.5, 11 Mbps
- 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)
- 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz & 160MHz)



## Technical Specifications

<b>Modulation</b>	<ul style="list-style-type: none"> <li>• 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz &amp; 160MHz)</li> </ul> Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
<b>Security<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 (personal) certification</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> </ul>
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>3</sup></b>	2.4GHz (MIMO, typical): <ul style="list-style-type: none"> <li>• 802.11b : +18dBm</li> <li>• 802.11g : +16.5dBm</li> <li>• 802.11n/ac/ax (HT20/VHT20/HE20) : +16dBm</li> <li>• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm</li> </ul> 5GHz (MIMO, typical): <ul style="list-style-type: none"> <li>• 802.11a : +13dBm</li> <li>• 802.11n/ac/ax (HT20/VHT20/HE20) : +13.5dBm</li> <li>• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm</li> <li>• 802.11ac/ax (VHT80/HE80) : +11.5dBm</li> <li>• 802.11ax HE160 : +11.5dBm</li> </ul> 6GHz LPI mode (MIMO, typical):: <ul style="list-style-type: none"> <li>• 802.11a : 0dBm</li> <li>• 802.11ax HE20 : +1 dBm</li> <li>• 802.11ax HE40 : +4dBm</li> <li>• 802.11ax HE80 : +7dBm</li> <li>• 802.11ax HE160 : +7.5dBm</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode :2.5 W</li> <li>• Receive mode :2 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode :50 mW (WLAN unassociated)</li> <li>• Connected Standby/Modern Standby: 10mW</li> <li>• Radio disabled: 8 mW</li> </ul>
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>4</sup></b>	2.4GHz (SISO): <ul style="list-style-type: none"> <li>• 802.11b, 11Mbps : -82dBm maximum</li> <li>• 802.11g, 54Mbps : -71 dBm maximum</li> <li>• 802.11n, MCS7 : -64dBm maximum</li> <li>• 802.11ac, MCS9 : -52dBm maximum</li> <li>• 802.11ax, MCS11(HT40): -49dBm maximum</li> </ul> 5GHz (SISO):

## Technical Specifications

- 802.11a, 54Mbps : -71 dBm maximum
- 802.11n, MCS07 : -64dBm maximum
- 802.11ac, MCS9 : -52dBm maximum
- 802.11ax, MCS11(HE80/HE160): -46dBm maximum

6GHz (SISO):

- 802.11a, 54Mbps : -71 dBm maximum
- 802.11n, MCS7 : -64dBm maximum
- 802.11ac, MCS9 : -52dBm maximum
- 802.11ax, MCS11(HE160): -46dBm maximum

<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	1. Type 2230: 2.8g 2. Type 126: 1.3g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	<b>Operating</b> 14° to 158° F (-10° to 70° C) <b>Non-operating</b> -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating</b> 10% to 60% (non-condensing) <b>Non-operating</b> 5% to 95% (non-condensing)
<b>Altitude</b>	<b>Operating</b> 0 to 10,000 ft (3,048 m) <b>Non-operating</b> 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	N/A

**HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card**

<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Signaling Data Rate</b>	Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps BLE: 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.
<b>Power Consumption</b>	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
<b>Bluetooth Software Supported Link Topology</b>	Microsoft Windows Bluetooth Software

## Technical Specifications

<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support
<b>Certifications</b>	FCC (47 CFR) Part 15C, Section 15.247 & 15.407
<b>Power Management</b>	ETS 300 328
<b>Certifications</b>	Low Voltage Directive CE Mark
<b>Bluetooth Software Supported</b>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising 2Mbps LE LE Long Range Windows BT profiles support BT5.3 Periodic Advertisement interval Encryption key size control enhancements

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

## Technical Specifications

<b>Intel® XMM™ 7560 R+ LTE-Advanced Pro<sup>1</sup></b>	<b>Technology/Operating bands</b>	FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 700 (Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1900 (Band 25), 850 (Band 26), 700 (Band 28), 700 (Band 29 RX only), 2300 (Band 30), 1700/2100 (Band 66), 600 (band 71). TDD LTE: 2100 (Band 34), 2600 (Band 38), 1900 (Band 39), 2400 (Band 40), 2500 (Band 41), 3500 (Band 42), 3700 (Band 43), 3700 (band 48), 5200 (Band 46 RX only) MHz; HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8) MHz
	<b>Wireless protocol standards</b>	3GPP Release 12 LTE Specification DL-CAT.16, DL 100MHz BW throughput up to 978Mbps; UL-CAT.13 40MHz throughput up to 150Mbps
	<b>GPS</b>	WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification
	<b>GPS bands</b>	Standalone GPS/Beidou/Glonass, A-GPS (MS-A, MS-B) 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
	<b>Maximum data rates</b>	LTE: 978 Mbps (Download), 150 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)
	<b>Maximum output power</b>	LTE: 23 dBm in all band except B41 LTE B41 HPUE = 26dBm HSPA+: 23.5 dBm
	<b>Maximum power consumption</b>	LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average)
	<b>Form Factor</b>	M.2, 3042-S3 Key B
	<b>Weight</b>	6 g
	<b>Dimensions (Length x Width x Thickness)</b>	42 x 30 x 2.3 mm
	<b>embedded eSIM</b>	Support

1. Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

## Technical Specifications

<b>NFC Mirage module (NXP NPC300 I2C 10mmx17mm)</b>	<b>Dimensions (L x W x H)</b>	Module 25 mm by 10 mm by 2.0 mm
	<b>Chipset</b>	NPC300
	<b>System interface</b>	I2C
	<b>NFC RF standards</b>	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
	<b>NFC Forum Support</b>	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2
	<b>Reader (PCD-VCD) Mode</b>	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz cards
	<b>Card Emulation (PICC-VICC) Mode</b>	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
	<b>Frequency</b>	13.56 MHz
	<b>NFC Modes Supported</b>	Reader/Writer, Peer-to-Peer
	<b>Raw RF Data Rates</b>	106, 212, 424, 848 kbps
	<b>Operating temperature</b>	0°C to 70°C
	<b>Storage temperature</b>	-20°C to 125°C
	<b>Humidity</b>	10-90% operating 5-95% non-operating
	<b>Supply Operating voltage</b>	4.35 to 5.25 Volts
	<b>I/O Voltage</b>	1.8V or 3.3V
	<b>Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)</b>	
	<b>Mode</b>	Power Consumption, Typical
	<b>Polling</b>	7.3 mA
	<b>Detected Test Tag Type 1</b>	Total 283.8 mA Net Module 236.8 mA
	<b>Detected Test Tag Type 2</b>	Total 288.8 mA Net Module 241.8 mA
	<b>Detected Test Tag Type 3</b>	Total 287.7 mA Net Module 240.7 mA
	<b>Detected Test Tag Type 4</b>	Total 282.3 mA Net Module 235.3 mA
<b>Antenna</b>	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.	

### Technical Specifications

<b>Realtek RTL8111FPH 10/100/1000 Integrated NIC</b>	<b>Connector</b>	RJ-45
	<b>System Interface</b>	PCIe + SMBus
	<b>Data rates supported</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
	<b>IEEE Compliance</b>	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet)
	<b>Performance</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling Jumbo Frame 9K
	<b>Power consumption</b>	Cable Disconnection: 25mW 100Mbps Full Run: 450mW 1000bp Full Run: 1000mW WoL Enable(S3/S4/S5): 50mW WoL Disable(S3/S4/S5): 25mW
	<b>Power Management</b>	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	<b>Management Interface IT Manageability</b>	Auto MDI/MDIX Crossover cable detection Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	<b>Security &amp; Manageability</b>	Support DASH 1.2 compliant

<b>Realtek RTL8111HSH 10/100/1000 Integrated NIC</b>	<b>Connector</b>	RJ-45
	<b>System Interface</b>	PCIe + SMBus
	<b>Data rates supported</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
	<b>IEEE Compliance</b>	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet)

### Technical Specifications

<b>Performance</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling Jumbo Frame 9K
<b>Power consumption</b>	Cable Disconnection: 25mW 100Mbps Full Run: 450mW 1000bp Full Run: 1000mW WoL Enable(S3/S4/S5): 50mW WoL Disable(S3/S4/S5): 25mW
<b>Power Management</b>	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
<b>Management Interface</b>	Auto MDI/MDIX Crossover cable detection
<b>IT Manageability</b>	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status

### Technical Specifications

#### POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors

<b>AC Adapter 45 Watt nPFC Standard USB Type C® Straight 1.8m</b>	<b>Dimensions (H x W x D)</b>	3.701 x 1.693 x 1.071 in (9.4x4.3x2.72cm)	
	<b>Weight</b>	0.44 lb (200 g) max (Not including power cord. Power cord varies by country.)	
	<b>Input</b>	100 ~ 240VAC	
	<b>Output</b>	<b>Input Efficiency</b>	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V: 81.5% 9V: 86.7% 12V: 87.4% 15V: 87.8%
		<b>Input frequency range</b>	47 ~ 63Hz
		<b>Input AC current</b>	Max. 1.4 A at 90 Vac
		<b>Output power</b>	5V/15W 9V/27W 12V/36W 15V/45W
		<b>DC output</b>	5V/9V/12V/15V
	<b>Connector</b>	<b>Hold-up time</b>	100% load 5ms at 115 Vac input
		<b>Output current limit</b>	<5.0A
<b>Environmental Design</b>		USB Type-C®	
<b>Operating temperature</b>		32°F to 95°F (0°to 35°C)	
<b>EMI and Safety Certifications</b>	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)	
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)	
	<b>Humidity</b>	20% to 95%	
	<b>Storage Humidity</b>	10% to 95%	
	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, USB-IF, Ukraine(CoC+DoC+RoHS+ECO)		

<b>AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m</b>	<b>Dimensions (H x W x D)</b>	3.74 x 1.772 x 1.043 in (9.5x4.5x2.65cm)
	<b>Weight</b>	0.44 lb (200 g) max (Not including power cord. Power cord varies by country)
	<b>Input</b>	100 ~ 240VAC
		<b>Input Efficiency</b>
<b>Input frequency range</b>		47 ~ 63 Hz
	<b>Input AC current</b>	Max. 1.4 A at 90 Vac



### Technical Specifications

<b>Output</b>	<b>Output power</b>	45W
	<b>DC output</b>	19.5V
<b>Connector</b>	<b>Hold-up time</b>	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input
	<b>Output current limit</b>	<8.0A
<b>Environmental Design</b>	<b>Connector</b>	4.5mm Barrel Type
	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
	<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

<b>AC Adapter 65 Watt nPFC Standard USB Type C® Straight 1.8m</b>	<b>Dimensions (H x W x D)</b>	3.543 x 2.008 x 1.122 in (9.0x5.1x2.85cm)
	<b>Weight</b>	0.53 lb (240 g) max (Not including power cord. Power cord varies by country.)
<b>Output</b>	<b>Input</b>	100 ~ 240VAC
	<b>Input Efficiency</b>	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 12V : 88% 15V : 88% 20V : 89%
	<b>Input frequency range</b>	47 ~ 63 Hz
	<b>Input AC current</b>	Max. 1.6 A at 90 Vac
	<b>Output power</b>	5V/15W 9V/27W 12V/60W 15V/60W 20V/65W
	<b>DC output</b>	5V/9V/12V/15V/20V
	<b>Hold-up time</b>	100% load 5ms at 115 Vac input
	<b>Output current limit</b>	<8.0A
	<b>Connector</b>	USB TYPE C®
	<b>Environmental Design</b>	<b>Operating temperature</b>

### Technical Specifications

<b>EMI and Safety Certifications</b>	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL 62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC	

<b>AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm</b>	<b>Dimensions (H x W x D)</b>	4.016 x 2.165 x 1.181 in (10.2x5.5x3cm)	
	<b>Weight</b>	0.58 lb (265 g) max (Not including power cord. Power cord varies by country.)	
<b>Input</b>	<b>Input</b>	100 ~ 240VAC	
	<b>Input Efficiency</b>	88.0 % at 115 Vac and 89.0 % at 230Vac	
	<b>Input frequency range</b>	47 ~ 63 Hz	
	<b>Input AC current</b>	Max. 1.7 A at 90 Vac	
	<b>Output</b>	<b>Output power</b>	65W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input
<b>Connector</b>	<b>Output current limit</b>	<11.0A	
<b>Environmental Design</b>	<b>Connector</b>	4.5mm Barrel Type	
	<b>Operating temperature</b>	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
		<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%	
	<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, BIS, UKCA DoC	

### Technical Specifications

<b>AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m</b>	<b>Dimensions (H x W x D)</b>	3.543 x 2.008 x 1.122 in (9.0x5.1x2.85cm)	
	<b>Weight</b>	0.55 lb (250 g) max (Not including power cord. Power cord varies by country.)	
	<b>Input</b>	100 ~ 240VAC	
	<b>Output</b>	<b>Input Efficiency</b>	88.0 % at 115 Vac and 89.0 % at 230Vac
		<b>Input frequency range</b>	47 ~ 63 Hz
		<b>Input AC current</b>	Max. 1.7 A at 90 Vac
		<b>Output power</b>	65W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input
	<b>Connector</b>	4.5mm Barrel Type	
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0° to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
		<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>		10% to 95%	
<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC		

<b>RH 42Whr Long Life Polymer Fast Charge 3 cell Battery <sup>1</sup></b>	<b>Weight</b>	0.18 kg (0.397 lb)	
	<b>Cells/Type</b>	3cell Lithium-Ion Polymer cell / 545974	
	<b>Energy</b>	<b>Voltage</b>	11.4V
		<b>Amp-hour capacity</b>	3.752Ah
		<b>Watt-hour capacity<sup>1</sup></b>	42.75Wh
	<b>Temperature</b>	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
		<b>Operating (Discharging)</b>	14° to 122° F (-10° to 60° C)
<b>Optional Travel Battery Available</b>		No	

### Technical Specifications

**RH 51Whr Long Life  
Polymer Fast Charge 3  
cell Battery<sup>1</sup>**

<b>Weight</b>	0.2025 kg (0.446 lb)
<b>Cells/Type</b>	3cell Lithium-Ion Polymer cell / 566075
<b>Energy</b>	<b>Voltage</b> 11.58V
	<b>Amp-hour capacity</b> 4.431Ah
	<b>Watt-hour capacity<sup>1</sup></b> 51.3Wh
<b>Temperature</b>	<b>Operating (Charging)</b> 32° to 113° F (0° to 45° C)
	<b>Operating (Discharging)</b> 14° to 122° F (-10° to 60° C)
	<b>Optional Travel Battery Available</b> No

---

## Technical Specifications

### AUDIO

<b>HD Stereo Codec</b>	ALC3247-CG
<b>Audio I/O Ports</b>	Headset: CTIA only and Headphone-out
<b>Internal Speaker Amplifier</b>	ALC 3247 has Embedded Class-D 2W Stereo Amplifier
<b>Multi-streaming Capable</b>	Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behavior
<b>Sampling</b>	Streams to be sent to/from the front and rear jacks or integrated speaker.
<b>Wavetable Syntheses</b>	Independent sampling rates for DAC's and ADC's; supports resolutions from 16 to 24-bit; 44.1 kHz: External MIC/internal MIC 16bit,48000Hz: External SPK/Internal SPK
<b>Analog Audio</b>	Support 3.5mm Headset: CTIA only and Headphone-out
<b># of Channels on Line-Out</b>	N/A
<b>Internal Speaker</b>	Yes

---

### FINGERPRINT READER

<b>Sensor vendor</b>	ELAN 80ST
<b>Sensor type</b>	Capacitive
<b>DPI resolution</b>	508 DPI
<b>Scan area</b>	80x80 pixels
<b>False Rejection Rate</b>	<3%
<b>False Acceptance Rate</b>	< 0.001%
<b>Mobile Voltage Operation</b>	2.7~3.6V
<b>Operating Temperature</b>	-20°C - +80°C
<b>Current Consumption</b>	35mA peak
<b>Image</b>	
<b>Low Latency Wait For Finger</b>	900uA
<b>Capture Rate</b>	Capture Rate: 50 frame/sec
<b>ESD Resistance</b>	IEC 61000-4-2 4B (+15KV)
<b>Detection Matrix</b>	508 dpi / 4x4mm sensor area

---

### Technical Specifications

#### ENVIRONMENTAL DATA

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• US Federal Energy Management Program (FEMP)</li> <li>• EPEAT® Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> <li>• TCO Certified</li> <li>• China Energy Conservation Program (CECP)</li> <li>• China State Environmental Protection Administration (SEPA)</li> <li>• Taiwan Green Mark</li> <li>• Korea Eco-label</li> <li>• Japan PC Green label*</li> </ul>		
<b>Sustainable Impact Specifications</b>	<ul style="list-style-type: none"> <li>• <a href="http://hp.com">Product Carbon Footprint (hp.com)</a></li> <li>• Ocean-bound plastic in Speaker</li> <li>• 5% post-consumer recycled plastic</li> <li>• 50% recycled metal</li> <li>• Low halogen</li> <li>• Outside Box and corrugated cushions are 100% sustainably sourced and recyclable</li> <li>• Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable</li> <li>• Bulk packaging available</li> </ul>		
<b>System Configuration</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.</p>		
<b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Sort idle)	5.57 W	5.47 W	5.01 W
Normal Operation (Long idle)	0.95 W	1.31 W	1.23 W
Sleep	0.95 W	1.31 W	0.84 W
Off	0.3 W	0.3 W	0.28 W
	<p><b>NOTE:</b> Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	19.0 BTU/hr	18.7 BTU/hr	17.1 BTU/hr
Normal Operation (Long idle)	3.2 BTU/hr	4.5 BTU/hr	4.2 BTU/hr
Sleep	3.2 BTU/hr	4.5 BTU/hr	2.9 BTU/hr
Off	1.0 BTU/hr	1.0 BTU/hr	1.0 BTU/hr
	<p><b>*NOTE:</b> Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>		

### Technical Specifications

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	2.6	14.3	
Fixed Disk – Random writes	2.6	14.3	
Optical Drive – Sequential reads	3.6	25.6	
<b>Longevity and Upgrading</b>	This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.		
<b>Additional Information</b>	<ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product is 93.3% recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	230 g
		PAPER/Paperboard	51 g
		PAPER/Molded Pulp	61 g
	<b>Internal:</b>	PLASTIC/Polyethylene low density-LDPE	9 g
	The plastic packaging material contains at least 0.0% recycled content.		
	The corrugated paper packaging materials contains at least 57.0% recycled content.		
<b>RoHS Compliance</b>	<p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.</p> <p>To obtain a copy of the HP RoHS Compliance Statement, see <a href="#">HP RoHS position statement</a>.</p>		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html">http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html</a>):</p> <ul style="list-style-type: none"> <li>Asbestos</li> <li>Certain Azo Colorants</li> <li>Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>Cadmium</li> </ul>		

### Technical Specifications

	<ul style="list-style-type: none"> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Bis(2-Ethylhexyl) phthalate (DEHP)</li> <li>• Benzyl butyl phthalate (BBP)</li> <li>• Dibutyl phthalate (DBP)</li> <li>• Diisobutyl phthalate (DIBP)</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>
<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842">http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>



### Technical Specifications

<b>footnotes</b>	<ul style="list-style-type: none"><li>• Percentage of ocean-bound plastic contained in each component varies by product</li><li>• Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.</li><li>• External power supplies, WWAN modules, power cords, cables and peripherals excluded.</li><li>• 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.</li><li>• Fiber cushions made from 100% recycled wood fiber and organic materials.</li><li>• Plastic cushions are made from &gt;90% recycled plastic.</li><li>• Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams</li></ul>
------------------	---

### COUNTRY OF ORIGIN

China

### Options and Accessories (Sold separately and availability may vary by country)

#### DOCKING (Sold Separately)

<b>Docking station model #1</b>	HP Thunderbolt 120W G4 Dock
<b>Total number of supported displays (incl. the notebook display)</b>	4
<b>Max. resolutions supported</b>	Quad 4K @60Hz Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode
<b>Dock Connectors</b>	2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode
<b>Technical limitations</b>	Maximum resolution and display support is dependent on the maximum capability of the notebook. Thunderbolt Hosts: Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host. Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz Non-Thunderbolt hosts: The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is (1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

<b>Docking station model #2</b>	HP Thunderbolt 280W G4 Dock
<b>Total number of supported displays (incl. the notebook display)</b>	4
<b>Max. resolutions supported</b>	Quad 4K @60Hz Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode
<b>Dock Connectors</b>	2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode
<b>Technical limitations</b>	Maximum resolution and display support is dependent on the maximum capability of the notebook. Thunderbolt Hosts: Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host. Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz Non-Thunderbolt hosts: The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is (1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

<b>Docking station model #3</b>	HP USB-C Dock G5
---------------------------------	------------------

### Options and Accessories (Sold separately and availability may vary by country)

<b>Total number of supported displays (incl. the notebook display)</b>	3
<b>Max. resolutions supported</b>	Dual 5K@ 30Hz + (1) 4K UHD (multi-function mode)
<b>Dock Connectors</b>	1xHDMI, 2xDP
<b>Technical limitations</b>	<p>Maximum resolution and display support is dependent on the maximum capability of the notebook.</p> <p>Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode.</p> <p>Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode</p> <p>The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.</p>
<b>Docking station model #4</b>	HP USB-C/A Universal Dock G2
<b>Total number of supported displays (incl. the notebook display)</b>	3
<b>Max. resolutions supported</b>	Dual 4K @ 60Hz Single 5K @ 60Hz
<b>Dock Connectors</b>	1xHDMI, 2xDP
<b>Technical limitations</b>	<p>Maximum resolution and display support is dependent on the maximum capability of the notebook.</p> <p>The best resolution for dual or triple displays is 4K UHD@ 60Hz.</p> <p>For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from the host.</p>
<b>Docking station model #5</b>	HP USB-C G5 Essential Dock
<b>Total number of supported displays (incl. the notebook display)</b>	3
<b>Max. resolutions supported</b>	<p>For hosts that support DisplayPort 1.4 with Display Stream Compression:</p> <p>3x FHD @ 60 Hz 3x QHD @ 60 Hz 3x 4K @ 60 Hz</p> <p>For hosts that support DisplayPort 1.3/1.4:</p> <p>3x FHD @ 60 Hz 3x QHD @ 60 Hz 2x 4K @ 60 Hz</p>
<b>Dock Connectors</b>	1 x HDMI, 2 x DP
<b>Technical limitations</b>	Video resolution depends on the capability of the host machine. This dock provides up to 65W of power delivery to the host machine.

### Options and Accessories (Sold separately and availability may vary by country)

Type	Description	Part Number
<b>Audio</b>	HP Wired USB-A Stereo Headset	428K6AA
	HP Wired 3.5mm Stereo Headset	428K7AA
	HP 365 BT Speaker	567D3AA#ACJ
<b>Video</b>	HP 325 FHD USB-A Webcam	53X27AA
	HP 965 4K USB-A STR Webcam	695J5AA
<b>Cases</b>	HP Prelude G2 15.6 Backpack	1E7D6AA
	HP Prelude G2 15.6 Top Load	1E7D7AA
	HP Prelude Pro Recycled 15.6 Backpack	1X644AA
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA
	HP Renew 14 Laptop Sleeve	2E6U9AA
	HP Renew Business 14.1 Laptop Bag	3E5F9AA
	HP Renew Business 14.1 Laptop Sleeve	3E2U7AA
	HP Renew Business 15.6 Laptop Bag	3E5F8AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Executive 14.1 Laptop Sleeve	6B8Y3AA
	HP Renew Executive 16 Laptop Backpack	6B8Y1AA
HP Renew Executive 16 Laptop Bag	6B8Y2AA	
<b>Docking</b>	HP USB-C 120W G5 Dock	5TW10AA
	HP USB-C/A 120W G2 Universal Dock	5TW13AA
	HP Thunderbolt 120W G4 Dock	4J0A2AA
	HP Thunderbolt 280W G4 Dock	4J0G4AA
<b>Hub</b>	HP 4K USB-C Multiport Hub	6G842AA
	HP Universal USB-C Multiport Hub	50H55AA
	HP USB-C Travel Dock G2	7PJ38AA
	HP USB-C to USB-A Hub	Z6A00AA
<b>Adapter</b>	HP USB-C to RJ45 Adapter G2	4Z527AA
	HP USB 3.0 to Gigabit RJ45 Adapter G2	4Z7Z7AA
	HP HDMI to VGA Adapter	H4F02AA
	HP USB-C to DisplayPort Adapter	N9K78AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to USB 3.0 Adapter	N2Z63AA
	HP USB-C to VGA Adapter	N9K76AA
<b>Keyboard/Combo</b>	HP 125 WD USB Keyboard	266C9AA
	HP 320K WD USB Keyboard	9SR37AA
	HP 355 Compact Multi-Device BT Keyboard	692S9AA
	HP 455 Programmable Wireless Keyboard	4R177AA

### Options and Accessories (Sold separately and availability may vary by country)

HP 975 USB+BT Dual-Mode Wireless Keyboard	3Z726AA
HP 155 Wired Mouse and Keyboard Combo	5B8C0AA#ACJ
HP 225 Antimicrobial Wired Mouse and Keyboard Combo	286K3AA#ABZ
HP 225 Wired Mouse and Keyboard Combo	286J4AA
HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA
HP 655 Wireless Keyboard and Mouse Combo	4R009AA
HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
HP Wireless Rechargeable 950MK Mouse and Keyboard	3M165AA

<b>Mouse</b>	HP 125 USB-A Wired Mouse	265A9AA
	HP 128 USB Laser Wired Mouse	265D9AA
	HP 155 USB-A Wired Mouse	5B8B7AA#ACJ
	HP 235 Wireless 2.4GHz Slim Wireless Mouse	4E407AA
	HP 320M USB-A Wired Mouse	9VA80AA
	HP 435 Bluetooth 5.0 + Wireless 2.4GHz Multi-Device Wireless Mouse	3B4Q5AA
	HP 715 Rechargeable Multi-Device Bluetooth 5.0 + Wireless 2.4GHz Bluetooth Mouse	6E6F0AA
	HP 925 Ergonomic Vertical Bluetooth 5.0 + Wireless 2.4GHz Wireless Mouse	6H1A5AA
	HP Creator USB-A+Bluetooth 935 Wireless Mouse Black	1DOK8AA
	HP USB Premium Wireless Mouse	1JR31AA
	HP USB-A+Bluetooth Multi-Device 635 Wireless Mouse Black	1DOK2AA
	HP USB-A+Bluetooth Travel Bluetooth Mouse	6SP30AA

<b>Power</b>	HP 45W USB-C LC Dali AC Power Adapter	1MZ01AA
	HP 65W 4.5 mm Smart AC Power Adapter	H6Y89AA
	HP 65W GaN USB-C Laptop Charger	600Q7AA
	HP 65W USB-C Laptop Charger	671R3AA
	HP 65W USB-C LC AC Power Adapter	1P3K6AA
	HP 90W 4.5 mm Smart AC Power Adapter	H6Y90AA

<b>Commodity</b>	HP USB DVD-Writer EXT ODD	F2B56AA
	HP Nano Keyed Cable Lock	1AJ39AA
	HP Nano Master Keyed Cable Lock	1AJ40AA
	HP SureKey Standard/Nano/Wedge Cable Lock	6UW42AA
	HP Combination Nano Cable Lock	63B28AA
	HP Essential Combination Nano Cable Lock	63B31AA

### Change Log

<b>Date of change:</b>	<b>Version History:</b>		<b>Description of change:</b>
March 2, 2023	V1 to V2	Added	Environmental Data
March 9, 2023	V2 to V3	Added	Battery life and Docking station
March 30, 2023	V3 to V4	Updated	At a Glance section
June 5, 2023	V4 to V5	Updated	Storage and Drives section
June 27, 2023	V5 to V6	Updated	HP Sure Recover disclaimer
August 1, 2023	V6 to V7	Updated	Environmental Data
October 3, 2023	V7 to V8	Updated	Frequency bands for Realtek 8852CE in Networking section
	V8 to V9		

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.